

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 964 365 A3**

(12)

**EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
31.10.2001 Bulletin 2001/44

(51) Int Cl.7: **G06T 11/00**

(43) Date of publication A2:  
15.12.1999 Bulletin 1999/50

(21) Application number: **99110969.5**(22) Date of filing: **09.06.1999**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Ratnaker, Viresh**  
**Sunnyvale, California 94086 (US)**

(74) Representative: **Grünecker, Kinkeldey,  
Stockmalr & Schwanhäusser Anwaltssozietät  
Maximilianstrasse 58  
80538 München (DE)**

(30) Priority: **11.06.1998 US 96719**

(71) Applicant: **SEIKO EPSON CORPORATION**  
**Shinjuku-ku, Tokyo 163-0811 (JP)**

**(54) Image delivery and display system**

(57) An image delivery and display system embodying a technique for displaying on a client computer of a client-server network a portion of an image stored on the server. Upon receiving a request from the client computer specifying particular x, y coordinates, the server decompresses the image to extract the area of interest, partitions the image area into tiles and extracts the tile

containing the x, y coordinates and a certain number of surrounding tiles, recompresses those tiles and transmits those tiles to the client computer. The tile containing the x, y coordinates is extracted, recompressed and transmitted first followed by the surrounding tiles in spiral order. The client computer then decompresses and displays the tiles in that same order.




Fig. 2

**EP 0 964 365 A3**



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 99 11 0969

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.8)
A	EP 0 341 645 A (HONEYWELL INC) 15 November 1989 (1989-11-15) * column 5, line 18 - column 6, line 32 * * column 8, line 18 - line 53 * * column 17, line 28 - column 19, line 16 * * figures 1,2,8,9 *	1-13	G06T11/00
A	GB 2 204 468 A (RACAL RADAR & DISPLAYS LTD) 9 November 1988 (1988-11-09) * page 1, paragraph 2 * * page 4, paragraph 3 * * page 5, paragraph 6 - page 7, paragraph 1 * * page 11, line 3 - page 13, paragraph 1 * * figures 1-4 *	1,2,5,6, 9,10,13	
A	EP 0 502 643 A (FUJITSU LTD) 9 September 1992 (1992-09-09) * page 5, line 25 - page 6, line 58; figures 1,4,5 *	1,5,9,13	
			TECHNICAL FIELDS SEARCHED (Int.Cl.8)
			G09G G06F G09B G01C
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 11 September 2001	Examiner Farricella, L
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons</p> <p>&amp; : member of the same patent family, corresponding document</p>			

EP 0 964 365 A3 (1999-11-15)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 11 0969

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

11-09-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0341645 A	15-11-1989	US 4876651 A	24-10-1989
		CA 1306059 A	04-08-1992
		DE 68928686 D	09-07-1998
		DE 68928686 T	14-01-1999
		JP 2049110 A	19-02-1990
		JP 2819469 B	30-10-1998
GB 2204468 A	09-11-1988	NONE	
EP 0502643 A	09-09-1992	JP 2671619 B	29-10-1997
		JP 4277871 A	02-10-1992
		DE 69211185 D	11-07-1996
		DE 69211185 T	02-10-1996
		US 5442734 A	15-08-1995

EPO FORM P0315

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82



(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 964 365 A2

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
15.12.1999 Bulletin 1999/50

(51) Int. Cl.<sup>6</sup>: G06T 11/00

(21) Application number: 99110969.5

(22) Date of filing: 09.06.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(30) Priority: 11.06.1998 US 96719

(71) Applicant:  
SEIKO EPSON CORPORATION  
Shinjuku-ku, Tokyo 163-0811 (JP)

(72) Inventor: Ratnaker, Viresh  
Sunnyvale, California 94086 (US)

(74) Representative:  
Grünecker, Kinkeldey,  
Stockmair & Schwanhäusser  
Anwaltssozietät  
Maximilianstrasse 58  
80538 München (DE)

### (54) Image delivery and display system

(57) An image delivery and display system embodying a technique for displaying on a client computer of a client-server network a portion of an image stored on the server. Upon receiving a request from the client computer specifying particular x, y coordinates, the server decompresses the image to extract the area of interest, partitions the image area into tiles and extracts the tile containing the x, y coordinates and a certain

number of surrounding tiles, recompresses those tiles and transmits those tiles to the client computer. The tile containing the x, y coordinates is extracted, recompressed and transmitted first followed by the surrounding tiles in spiral order. The client computer then decompresses and displays the tiles in that same order.




Fig. 2

EP 0 964 365 A2

## Description

### BACKGROUND OF THE INVENTION

#### Field of the Invention

[0001] This invention relates generally to an image delivery and display system, and more particularly to a technique for retrieving tiled image data that may be used, for example, in connection with a client-server network, wherein a center tile of the requested image is transmitted and displayed on the client computer first followed by the surrounding tiles in spiral order.

#### Description of the Related Art

[0002] In a client-server network, the server is a relatively large computer which manages files and databases for smaller client computers and also controls the interconnecting networks. A client-server network may be used, for example, in connection with a navigation system wherein a stationary server computer stores a street map covering the entire United States and a client computer on-board a vehicle accesses some portion of that map by specifying certain x, y map coordinates.

[0003] Upon receiving the specified x, y coordinates from the client computer, the server (which typically stores the map image in compressed form) decompresses the map image, partitions the image into tiles, extracts the tile containing the x, y coordinates and a certain number of surrounding tiles, recompresses those tiles and transmits this map data to the client computer. Upon receiving the compressed map data, the client computer decompresses the data and displays the map on the screen. The problem is that the tiles are typically decompressed and displayed from left to right, top to bottom, as indicated by the arrows on the tiled map image 11 shown in Fig. 1. Since the tile containing the x, y coordinates is in or near the middle, some time elapses before the client computer actually displays the tile containing the x, y coordinates, which is the tile of most interest to the operator of the vehicle.

[0004] Various proposals have been made for capturing, storing, transmitting and/or displaying images in connection with on-board navigation or display systems and/or map generating systems. However, none of these proposals solve the aforementioned problem.

[0005] In U.S. Patent Nos. 4,630,065 and 4,660,037, devices have been developed for visually indicating the current location of an automotive vehicle. A mechanism assesses the coordinates of the moving vehicle using its direction and distance traveled, and displays the vehicle coordinates along with a map of the region. In the first patent, a series of local maps of an extended area are stored on microfilm as a photographic image collection and are individually available for viewing on a display. In the second patent, the map image information of the extended area is stored in digital form such

that a portion of the map may be accessed for viewing.

[0006] On-board navigation systems have also been proposed for use in connection with aircraft. One such system is set forth in U.S. Patent No. 5,057,835. The map and text display system proposed therein offers several "functionality" features such as conditional display of text, runway orientations, etc. Another such system has been proposed in U.S. Patent No. 4,405,943. This patent provides a low bandwidth video imaging and transmission system that is used with a remotely piloted vehicle. High resolution images are captured in real time using a camera on an aircraft and then transferred to a memory aboard the aircraft. To reduce bandwidth, only a selected portion of the image is retrieved from ground as high resolution data; the remaining portion is retrieved as low resolution data. Another digital map display system for an aircraft is set forth in U.S. Patent No. 4,876,651. This system includes a mass memory unit and a cache memory with display and map data transfer occurring in parallel.

[0007] Another patent directed to an electronic global map generating system is U.S. Patent No. 4,972,319. The system therein uses a hierarchical tiling scheme. Map data is organized into a hierarchy of successive magnitudes for storage and presentation of map images at various resolutions.

[0008] However, none of these patents teach or suggest a tiled-image delivery and display system with a spirally rendered presentation of the tiles beginning with a center tile.

#### Objects of the Invention

[0009] It is therefore an object of this invention to overcome the aforementioned problems with image delivery and display systems.

[0010] It is another object of this invention to provide an access mechanism which retrieves a center tile of a tiled-image first followed by the other tiles in a spiral order.

[0011] It is still another object of this invention to provide an image delivery and display system for more efficiently transferring map imagery over a network in a tiled manner.

#### SUMMARY OF THE INVENTION

[0012] According to one aspect of the invention, a method of delivering image data, such as map image data, from a storage system to a display is provided. The method comprises the steps of: requesting, for display, at least a portion of the image stored in the storage system by specifying coordinates defining a location in requested image; partitioning the image into a plurality of tiles including a middle tile containing the location defined by the specified coordinates and a plurality of surrounding tiles; extracting the middle tile first followed by a plurality of surrounding tiles; and displaying the

requested image, wherein the middle tile is displayed first followed by the plurality of surrounding tiles in spiral order.

[0013] The method may be embodied in a computer-usable medium such as software or hardware and may be carried out on a computer system or client-server network.

[0014] Other objects and attainments together with a fuller understanding of the invention will become apparent and appreciated by referring to the following description and claims taken in conjunction with the accompanying drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

[0015] In the drawings wherein like reference symbols refer to like parts:

Fig. 1 is a schematic diagram showing the order in which tiled image data is conventionally transmitted and displayed.

Fig. 2 schematically illustrates a client-server computer system for use in connection with the invention.

Fig. 3 is schematic illustration of a computer system on which the present invention may be implemented.

Fig. 4 is a schematic diagram showing the order in which tiled image data is transmitted and displayed in accordance with the invention.

Fig. 5 is a flow chart illustrating the algorithm of the present invention.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0016] Referring to Fig. 2, a client-server computer system 20 is depicted. The system 20 includes a plurality of personal computer systems, identified by the reference numerals 21, 22 and 23, which are connected to a telecommunications network 24 that delivers data from a more powerful computer system known as a server 25 where data is stored in a disk storage subsystem 26. The subsystem 26 includes storage devices 27, 28, 29 and a data processor 31 for packaging the data for efficient storage and retrieval.

[0017] A more detailed block diagram illustration of a computer which may be used in connection with the invention is shown in Fig. 3. The computer, identified generally by reference numeral 101, may be of any suitable type such as a main frame or personal computer and depicts an architecture that is representative of either a client computer or server. Computer 101 comprises a central processing unit (CPU) 102 which may be a conventional microprocessor, a random access memory (RAM) 103 for temporary storage of information, and a read only memory (ROM) 104 for permanent storage of information. Each of these components is

coupled to a bus 105. Operation of the computer 101 is typically controlled and coordinated by operating system software. The operating system, which is embodied in the system memory and runs on CPU 102, coordinates the operation of computer system 101 by controlling allocation of system resources and performing a variety of tasks, such as processing, memory management, networking and I/O functions, among others.

[0018] Also coupled to bus 105 by a controller 106 is a diskette drive 107 into which a non-volatile mass storage device such as a diskette 108 may be inserted. Similarly, a controller 109 interfaces between bus 105 and a compact disc (CD) ROM drive 110 which is adapted to receive a CD ROM 111. A hard disk 112 is provided as part of a fixed disk drive 113 which is coupled to bus 105 by a disk controller 114.

[0019] A keyboard 115 and mouse 116, which are coupled to bus 105 via a controller 117, facilitate the input of data and otherwise provide a means for entering information into computer 101. Computer 101 also includes a display 118 and may further include a variety of peripheral devices such as a printer 119 and a scanner 120.

[0020] Referring to Figs. 2 and 3, in accordance with the invention, map image data is transferred to client computer 21, 22 and/or 23 from the remotely located server 25. Thus, each of these computers 21, 22 and 23 as well as the server 25, as illustrated on computer 101, include a communications adapter 121 which enables communication across networks 122, which may include local area networks (LANs), the internet or online services, via direct connections or via modem.

[0021] In accordance with the invention, an algorithm is provided that enables the tile containing the specified x, y coordinates to be extracted and transmitted first by the server 25 and decompressed and displayed first on client computer 21, 22 and/or 23. The surrounding tiles are then extracted, transmitted, decompressed and displayed in a spiral order, as indicated on the tiled map image 12 shown in Fig. 4. Thus, the tile containing the x, y coordinates (which is the tile containing the most pertinent information) is viewable on the client computer almost immediately after the server receives the request, thereby providing useful information to the driver of the vehicle without delay. The surrounding tiles then come into view in spiral order providing additional information concerning peripheral areas.

[0022] The underlying algorithm of the present invention is shown by way of a flow chart in Fig. 5. In step 201, the client computer user requests a portion of an image stored on the server by specifying x, y coordinates defining a particular location in the image and transmits this information to the server. For example, the server may store a map of the entire United States and the client computer user may wish to access only a portion of that map. Upon receiving the specified x, y coordinates, the server decompresses the image to extract the image area needed by the client and cen-

tered at the specified x, y coordinates in step 202. The server then partitions the decompressed image area into tiles in step 203. In step 204, the server first extracts the tile with the location defined by the x, y coordinates and then extracts a certain number of surrounding tiles in spiral order. These extracted tiles are recompressed by the server and transmitted to the client computer in the same order that they were extracted. Upon receiving the tiles, in step 206 the client computer decompresses and displays them in the same order they were extracted and transmitted. That is, the tile having the location defined by x, y coordinates is decompressed and displayed first followed by the surrounding tiles in spiral order.

[0023] While the invention has been described in conjunction with specific embodiments, it will be evident to those skilled in the art in light of the foregoing description that many further alternatives, modifications and variations are possible. Accordingly, the invention described herein is intended to embrace all such alternatives, modifications, applications and variations as may fall within the spirit and scope of the appended claims.

#### Claims

1. A method of delivering image data from a storage system to a display, comprising the steps of:

requesting, for display, at least a portion of an image stored in the storage system by specifying coordinates defining a location in at least the portion of the image requested;  
partitioning at least the portion of the image into a plurality of tiles including a first tile containing the location defined by the specified coordinates and a plurality of surrounding tiles;  
and  
displaying at least the portion of the image, wherein the first tile is displayed first followed by the plurality of surrounding tiles in spiral order.

2. The method of claim 1, wherein the first tile is a middle tile of at least the portion of the image.
3. The method of claim 1, further comprising the step of:

decompressing the image data stored in the storage system before partitioning at least the portion of the image.

4. The method of claim 3, further comprising the step of:

extracting the first tile and a plurality of surrounding tiles, after partitioning at least the por-

tion of the image, wherein the first tile is extracted first followed by the plurality of surrounding tiles in spiral order.

5. A computer system including a processor and a memory having a computer-readable program code embodied therein for causing the processor to display at least a portion of an image stored in a storage system by performing the steps of:

requesting, for display, at least the portion of an image stored in the storage system by specifying coordinates defining a location in at least the portion of the image requested;  
partitioning at least the portion of the image into a plurality of tiles including a first tile containing the location defined by the specified coordinates and a plurality of surrounding tiles;  
and  
displaying at least the portion of the image, wherein the first tile followed by the plurality of surrounding tiles in spiral order.

6. The computer system of claim 5, wherein the first tile is a middle tile of at least the portion of the image.

7. The computer system of claim 5, further comprising the step of:

decompressing at least the portion of the image before partitioning at least the portion of the image.

8. The computer system of claim 7, further comprising the step of:

extracting the first tile and a plurality of surrounding tiles, after partitioning at least the portion of the image, wherein the first tile is extracted first followed by the plurality of surrounding tiles in spiral order.

9. A computer-usable medium having a computer-readable program code embodied therein for causing a computer to display at least a portion of an image stored in a storage system by performing the steps of:

requesting, for display, at least a portion of an image stored in the storage system by specifying coordinates defining a location in at least the portion of the image requested;  
partitioning at least the portion of the image into a plurality of tiles including a first tile containing the location defined by the specified coordinates and a plurality of surrounding tiles;  
and



displaying at least the portion of the image,  
wherein the first tile is displayed first followed  
by the plurality of surrounding tiles in spiral  
order.

5

10. The computer usable medium of claim 9, wherein  
the first tile is a middle tile of at least the portion of  
the image.

11. The computer usable medium of claim 9, wherein 10  
the computer is further caused to perform the step  
of:

decompressing at least the portion of the 15  
image before partitioning at least the portion of  
the image.

12. The computer usable medium of claim 11, wherein  
the computer is further caused to perform the step  
of: 20

extracting the first tile and a plurality of sur-  
rounding tiles, after partitioning at least the por-  
tion of the image, wherein the first tile is  
extracted first followed by the plurality of sur- 25  
rounding tiles in spiral order.

13. A client-server computer system, comprising:

a server having an image stored therein; and 30  
at least one client computer connected to the  
server through a network;  
wherein a signal is sent from the client compu-  
ter to the server requesting, for display on the  
client computer, at least a portion of the image 35  
stored in the server by specifying coordinates  
defining a location in the image;  
wherein the server partitions at least the por-  
tion of the image requested into a plurality of  
tiles including a first tile containing the location 40  
defined by the specified coordinates and a plu-  
rality of surrounding tiles; and  
wherein the client computer displays at least  
the portion of the image by displaying the first  
tile followed by the plurality of surrounding tiles 45  
in spiral order.

50

55




Fig. 1  
(Prior Art)




Fig. 2




Fig. 3




Fig. 4




Fig. 5